WATERMARK SCOPE OF USE

BACKGROUND

The Scope of Use is a statement by the Approved User specifying the intended use of the product. The Scope of Use may include any limitations to the application of the product such water pressure, water temperature or any other operating circumstances.

The statement shall be included with the product when sold and shall be clearly visible and comprehensible to the intending purchaser and user. The statement may be stamped onto the product, printed on the packaging or included as part of the installation instructions.

Where it is not possible to include this statement as outlined it may be permissible to include advice that the statement is available from a website:

WATERMARK LICENCE: 1709

APPROVED USER: COP-A-MATE Products Pty Ltd

MODEL / DRANG	CCORE OF LICE	T
MODEL / BRAND	SCOPE OF USE	Form and manner in
IDENTIFICATION		which the statement
		shall be applied to the
		product
	Male Pressed Socket flange adaptor, DN40, MWP	Instructions
COP-A-MATE ACZPF040	2300 kPa	
	Male Pressed Socket flange adaptor, DN 50, MWP	Instructions
COP-A-MATE ACZPF050	1710 kPa	
	Male Pressed Socket flange adaptor, DN 65, MWP	Instructions
COP-A-MATE ACZPF065	1370 kPa	
	Male Pressed Socket flange adaptor, DN 80, MWP	Instructions
COP-A-MATE ACZPF080	1520 kPa	
	Male Pressed Socket flange adaptor, DN 100, MWP	Instructions
COP-A-MATE ACZPF100	1200 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTF100	adaptor, DN 100, MWP 1200 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTF125	adaptor, DN 125, MWP 960 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTF150	adaptor, DN 150, MWP 1000 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTF200	adaptor, DN 200, MWP 720 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTFO25	adaptor, DN 25, MWP 3500 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTFO32	adaptor, DN 32, MWP 2780 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTFO40	adaptor, DN 40, MWP 2300 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTFO50	adaptor, DN 50, MWP 1710 kPa	
	Copper Capillary Socket (Short engagement) flange	Instructions
COP-A-MATE ACZSKTFO65	adaptor, DN 65, MWP 1370 kPa	
COP-A-MATE ACZSKTFO80	Copper Capillary Socket (Short engagement) flange	Instructions

adaptor, DN 80, MWP 1520 kPa

Prepared by Approved User:

Company: COPAMATE PRODUCTS PTY LTD

Name CHANDRA SHANMUGAM Title: GENERAL MANAGER

Date 05/03/2021

ACCEPTED SCOPE OF USE

AGA CLIENT MANAGER Ivan Marsic DATE: 05/03/2021